

Nitrogen Dioxide Gas Sensor

(Model: MQ-E4-NO₂)

Manual

Version: 1.2

Valid from: 2014-05-01

Taiyuan Tengxing sensor technology Co., Ltd

Statement

1. The copyright of instructions belong to Taiyuan Tengxing sensor technology Co., Ltd(hereinafter referred to as the Company), nobody is allowed to copy, translate, spread or store without written approval.
2. Thanks for using our product. In order to use the products more smoothly, reduce faults result from inappropriate using, please read the instructions carefully before using and follow the rules suggested strictly. Anyone who don ' t follow the instructions, disassemble or change the internal components without permission will afford the loss.
3. The color, style and size of the product is subject to the object you received.
4. The company follows the idea of scientific and technological progress, make efforts to product-improving and technology-innovating. So we have the right to improve product without prior notice.
5. Please make sure it ' s valid before using the instructions. Any good suggestions from you is welcomed.
6. The instructions should be well kept.

Taiyuan Tengxing sensor technology Co., Ltd

MQ-E4-NO₂ Nitrogen Dioxide Gas Sensor

Profile

MQ-E4-NO₂ nitrogen dioxide gas sensor is constant potential electrolysis type. Oxidation-reduction reaction with nitrogen dioxide and oxygen take place respectively on the working electrode and on the counter electrode. The process releases electric charge and generates current. The current is in direct proportion to the concentration of nitrogen dioxide. So the concentration of the target gas could be got by measuring the value of current.


Features

Low power consumption, high precision, high sensitivity, wide linear range, good anti-interference ability, excellent repeatability and stability.

Main applications

It is used for nitrogen dioxide detection in industrial occasions, mine and environmental protection field.

Technical	nitrogen dioxide (NO ₂)
Detection Range	0~20ppm
Max range	150ppm
Sensitivity	(1.2±0.3) μA/ppm
Resolution	0.1ppm
Response Time(T ₉₀)	<30S
Bias Voltage	10Ω(recommended)
Load Resistance	0mV
Repeatability	<2% Output value
Stability(/month)	<2%
Output Linearity	Linear
Zero drift(-20℃~40℃)	0.2ppm
Temperature range	-20℃~50℃
Humidity range	15%~90% RH
Pressure range	standard atmospheric pressure±10%
Lifespan	2 years(in air)



Basic Circuit




Fig2: MQ-E4-NO₂ test circuit

Description of sensor characters




Fig3. Responce and Resume




Fig4. Linearity




Fig5. Output of sensor at different temperature




Fig6. Zero output of sensor at different temperature

Cross Interference

MQ-E2-NQ sensor also can respond to other gases besides target gas NO₂. Following data are the response characteristics of the sensor to interferential gases at certain concentration for your reference.

Interferential Gas	Concentration	MQ-E4-NO ₂
H ₂ S	15	<-3
CO	300	0
NO	35	0
Cl ₂	5	≈5
SO ₂	5	0
HCN	10	0
HCl	5	0
C ₂ H ₄	50	<5
NH ₃	20	<2

Cautions!

- Tin soldering is prohibited.
 - Before using, power on to aging for more than 48 hours is necessary.
 - Pins can't be broke off or bent.
 - Don't disassemble the sensor to avoid the damage caused by electrolyte leakage.
 - Avoid contacting organic solvent (including Silicone rubber and other adhesive), coatings, medicine, oil and high concentration gases.
 - All the electrochemical sensors shall not be encapsulated completely by resin materials, and shall not immerse in pure oxygen environment, otherwise, it will damage the function of sensor
 - All electrochemical sensors shall not be applied in corrosive gas environment, or the sensor will be damaged
 - Zero calibration should be finished in clean air.
 - During test and usage, sensors should avoid the gas inflow vertically
 - The side for inflow can't be choked and polluted.
 - The laminating film above the sensor surface can't be uncovered and damage.
-

-
- Excessive impact or vibration should be avoided
 - It takes some time for the sensor to return to normal state after it is applied in high concentration gas
 - Working electrode and reference electrode of the sensor shall be in short circuit when stored
 - Prohibit to use the hot cement or sealant of which the curing temperature is higher than 80°C to make the capsulation for the sensor.
 - Prohibit storage and usage for long time in alkaline gases with high concentration.
 - Do not use the sensor when the shell is damaged
-